

Setback Distances
Blue Earth County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
17	100	150	200	250
18	50	70	90	110
27	90	150	200	250
35	70	100	130	160
39	140	270	380	400
41	140	230	300	370
62	60	80	100	120
69	90	90	90	100
84	50	60	80	90
85	60	90	110	130
86	50	60	70	90
94	50	70	80	100
96	50	70	90	110
109	50	60	70	80
110	50	70	80	100
113	50	60	80	90
114	50	60	80	100
128	80	120	150	180
130	50	80	90	110
134	50	70	80	100
136	60	90	110	130
140	60	90	110	140
160	90	140	190	240
178	80	160	210	270
181	110	160	230	290
183	120	220	300	380
197	60	90	120	140
211	50	80	100	110
219	50	60	80	90
229	50	70	90	110
230	50	60	70	90
239	50	50	70	80
248	60	90	120	140
281	90	140	190	230
286	50	70	90	110

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances
Blue Earth County, Minnesota Table date: March 8, 2012

287	50	70	90	110
310	50	80	100	120
311	50	60	80	90
316	50	70	90	100
317	60	90	110	140
319	50	80	100	120
329	60	120	170	220
349	60	90	110	130
353	50	70	90	100
354	170	220	270	310
363	100	150	200	240
364	50	80	100	110
414	50	50	60	70
448	50	90	110	140
451	70	110	130	160
524	200	250	250	250
525	50	70	140	170
539	50	70	90	120
548	50	150	240	380
851	50	90	120	160
854	50	60	70	80
855	70	110	130	160
919	50	60	70	90
926	90	150	200	250
929	90	140	190	240
932	50	60	80	100
941	60	90	120	140
946	100	180	250	320
947	60	90	110	130
968	50	60	80	90
978	50	60	70	80
996	50	80	100	120
997	50	70	80	100
998	50	70	90	110
1001	50	70	90	120
1002	50	70	100	120
1004	60	90	120	140
1053	50	70	80	90

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances
Blue Earth County, Minnesota Table date: March 8, 2012

1800	200	250	300	350
101B	60	90	110	130
101C	60	90	110	130
102B	50	70	90	110
102C	50	70	90	110
105B	50	60	80	90
105C	50	60	80	90
106B	50	60	80	100
106C	50	60	80	100
128B	80	120	150	180
138B2	50	80	100	120
138C2	50	80	100	120
1801B	80	130	170	210
222B	100	160	200	240
238B	60	80	100	120
238C	60	80	100	120
259B	60	90	110	140
275B	50	60	80	100
27B	100	160	210	260
39B	140	270	380	400
41B	140	230	300	380
41C	140	230	300	380
69B	90	90	90	100
856B	50	70	80	100
909C	70	110	130	160
920B	50	70	90	110
920C	50	70	90	110
921C	50	70	90	110
94B	50	70	80	100
94C	50	70	80	100
96B	50	70	90	110
96C	50	70	90	110
L13A	50	90	120	140
L84A	50	60	70	90
L85A	50	60	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.