

Setback Distances in feet  
 Carver County, Minnesota      Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
AA	120	220	300	370
AB2	140	240	320	400
BA	130	270	380	400
BB2	150	280	390	400
BH	80	120	150	180
BY	110	200	280	350
CC3	50	60	80	90
CD3	50	60	80	90
CE3	50	60	80	90
CH	50	60	80	100
CL	50	50	70	80
CO	50	70	90	110
CS	50	70	90	110
CT	50	70	80	100
CU	50	50	70	80
CW	50	70	90	110
DA	110	200	270	350
DB	110	200	270	350
EA	130	210	280	350
EB	130	210	280	350
EB2	140	220	290	360
FA	130	240	330	400
FB	130	240	330	400
GL	50	60	70	90
HM	50	60	80	100
HN	80	120	170	210
IA	110	190	250	320
IB2	110	190	250	320
KB	60	80	100	120
KB2	50	70	90	100
KL	60	90	110	130
KM	140	220	280	350
LA	50	70	90	110
LB2	50	70	90	100
LC	50	60	80	90

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
 Carver County, Minnesota      Table date: March 8, 2012

LD	50	60	80	90
LF	50	60	80	90
LS	50	70	90	110
MK	50	70	80	90
MN	70	110	140	170
MP	50	70	80	90
MY	140	260	360	400
OS	50	70	80	100
PA	130	200	260	320
PB	130	200	260	320
PM	50	70	80	90
PS	50	70	80	90
RB	110	230	320	400
RW	50	130	190	250
SV	50	50	60	80
TB	50	70	90	110
TT	110	200	270	340
WA	120	220	300	380
WA	120	220	300	380
WB	120	220	300	380
WB	120	220	300	380
XB	110	230	320	400
YB	110	230	320	400

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.