

Setback Distances in feet  
Cass County, Minnesota      Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
48	100	160	210	270
147	60	90	120	140
202	130	210	270	330
243	50	50	70	80
292	50	70	100	120
540	50	70	80	90
541	200	250	300	350
543	50	110	200	290
544	50	70	80	90
549	200	250	300	350
564	160	250	320	390
684	130	230	320	400
788	50	70	80	90
797	200	250	300	350
799	50	70	80	90
1002	50	70	80	90
1943	130	210	270	330
1996	150	240	320	390
126B	140	210	280	340
158B	120	180	230	280
167B	70	100	130	160
1995B	150	270	370	400
204B	60	90	120	140
240A	60	80	90	100
240B	50	70	80	90
268B	170	280	370	400
454B	150	240	310	380
458A	130	210	270	330
458B	140	220	280	340
665B	120	190	260	320
730A	170	280	380	400
730B	170	280	380	400
731A	150	260	360	400
731B	140	250	340	400
773B	60	80	100	110

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
Cass County, Minnesota      Table date: March 8, 2012

7A	130	220	310	370
7B	130	220	310	370
870B	70	100	130	150
A10	50	80	100	120
A12	50	70	80	90
A15	120	190	250	300
A16	80	100	120	140
E57	120	180	230	280
E58	150	230	290	350
E59	50	70	80	100
E60	60	80	100	110
E62	60	80	100	110
E65	60	80	100	110
F76	60	80	100	110
K22	140	220	280	330
K27	50	60	80	90
K28	70	100	130	160
K30	50	50	60	70
K31	50	60	80	90
K35	50	60	80	90
N77	150	230	290	360
N78	150	220	rev	340
O92	120	180	230	290
O94	130	200	260	320
O96	160	270	350	400
O97	160	250	320	400
X01	50	70	80	90

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.