

Setback Distances in feet
Chippewa County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
35	60	90	110	130
60	70	100	120	140
85	60	90	110	130
89	110	200	270	340
113	50	60	70	90
234	50	60	80	90
246	160	280	370	400
338	50	70	90	110
344	50	80	90	110
371	70	110	150	180
423	50	70	80	100
434	50	70	90	110
444	50	60	70	90
574	50	60	80	90
597	50	70	90	110
610	60	80	100	120
847	50	80	100	120
881	60	90	110	130
1802	60	90	110	130
1866	50	60	80	90
1868	50	60	70	80
127A	120	200	270	340
127B	130	210	280	340
141A	90	140	190	230
141B	90	140	190	230
1864B	50	60	80	100
290B	110	170	220	270
324B	70	100	130	150
339A	140	250	340	400
339B	150	250	350	400
341B	170	280	370	400
421B	50	70	80	100
45B	170	270	350	400
591B	50	60	80	90
891B2	50	60	80	90

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Chippewa County, Minnesota Table date: March 8, 2012

94B	50	60	80	90
957B2	100	160	210	260
J101B	50	60	80	100
J11A	50	60	70	90
J12A	160	300	400	400
J15B	80	130	170	210
J17A	50	70	90	100
J18A	90	150	200	240
J1A	50	50	70	80
J20A	100	170	230	280
J23A	50	80	100	120
J256A	50	70	90	110
J260A	50	70	90	100
J261A	50	60	80	90
J26B	50	70	90	100
J27A	70	110	150	180
J2A	50	80	100	120
J30A	50	70	100	110
J31B	170	290	400	400
J32A	50	70	80	100
J34B	50	80	100	110
J35B	50	60	80	100
J38B	80	120	160	190
J41A	100	140	170	200
J46B	50	70	90	110
J48A	50	60	80	100
J50A	50	60	80	100
J51A	50	70	90	110
J52A	60	100	120	150
J53A	50	80	110	130
J56A	50	60	80	90
J57A	50	60	80	100
J58B	100	170	240	290
J64A	50	80	100	110
J6A	100	200	290	360
J75A	140	250	340	400
J75B	140	250	340	400
J77A	50	80	100	120

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Chippewa County, Minnesota Table date: March 8, 2012

J7A	100	180	240	300
J7B	100	180	240	300
J8A	90	140	190	230
J8B	90	150	190	230
J9A	140	280	390	400

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.