

Setback Distances in feet
Dodge County, Minnesota Table date: March 6, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
1027A	50	70	100	120
1033A	50	60	80	100
L171A	50	60	80	90
L177B	50	70	80	100
L180A	50	60	70	90
L181A	50	80	90	110
L182A	50	60	80	90
L183B	50	60	70	90
L183C2	50	60	70	90
L190B	110	220	310	400
L190C2	110	220	310	400
L57A	50	210	320	400
M502A	110	220	310	400
M504A	140	260	360	400
M505A	50	70	80	90
M506B	50	50	60	70
M507A	50	60	70	80
M507B	50	60	70	80
M508A	50	60	70	80
M509A	120	220	310	380
M509B	120	220	310	380
M509C2	120	220	310	380
M510A	50	60	70	80
M511A	50	60	70	90
M512A	100	200	280	360
M513A	120	250	350	400
M514A	110	220	310	400
M515A	50	50	60	70
M517A	50	60	80	90
M518B	50	60	80	90
M521C2	50	60	70	80
M523C2	50	60	70	80
M524A	140	270	370	400
M525A	130	250	350	400
M532A	50	60	70	80

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Dodge County, Minnesota Table date: March 6, 2012

M533A	140	260	360	400
N501B	60	90	110	140
N501C2	60	90	110	140
N514B	60	90	120	140
N522A	70	100	130	150
N536B	60	90	110	140
N536C2	60	90	110	140
N538C2	60	90	90	90
N552B	50	50	50	50
N555B	60	90	110	140
N555C2	60	90	110	140
N572B	60	90	110	140
N572C2	60	90	110	140
N574B	60	90	110	140
N574C2	60	90	110	140
N578B	70	110	140	170
N595A	70	100	130	150

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.