

Setback Distances in feet
 Hennepin County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
D10A	110	210	280	360
D11A	60	90	120	140
D12B	60	100	120	150
D15A	50	70	80	90
D16A	50	70	80	90
D17A	140	240	320	400
D19A	120	210	290	360
D1B	160	250	320	390
D20A	110	210	290	360
D21A	110	210	290	360
D23A	60	140	260	350
D24A	80	210	310	390
D25A	130	220	300	370
D2A	110	250	350	400
D30A	50	70	80	90
D35A	140	270	370	400
D3A	140	270	370	400
D43A	50	70	80	100
D4A	150	260	340	400
D4B	150	260	340	400
D5B	130	250	350	400
D6A	130	230	310	380
D6B	130	230	310	380
D7A	130	250	350	400
D7B	150	270	360	400
D8B	160	280	390	400
L10B	140	240	330	400
L11B	50	80	100	120
L131A	110	170	210	250
L132A	50	60	80	100
L13A	50	90	120	140
L14A	50	70	80	90
L15A	50	70	80	90
L16A	50	70	80	90
L17B	50	60	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Hennepin County, Minnesota Table date: March 8, 2012

L18A	50	70	90	100
L21A	50	80	90	110
L23A	50	70	90	110
L24A	50	60	80	100
L25A	50	70	90	110
L26A	50	70	90	100
L26B	50	70	90	100
L27A	100	170	230	280
L28A	60	100	130	150
L29A	60	100	140	180
L2B	140	260	370	400
L30A	50	70	80	90
L30A	50	70	80	90
L31A	50	70	80	90
L35A	60	80	100	120
L36A	50	70	90	110
L37B	50	60	80	100
L38A	70	100	130	150
L39A	100	160	200	250
L3A	110	230	320	400
L3B	110	230	320	400
L40B	50	60	80	100
L42B	60	100	120	150
L43A	60	100	130	150
L44A	50	70	90	100
L45A	50	80	100	120
L46A	90	190	260	330
L47A	150	260	360	400
L47B	150	260	360	400
L49A	50	70	80	90
L4B	100	160	250	330
L50A	50	70	80	90
L56A	50	70	80	90
L58B	70	100	120	140
L59A	70	120	150	190
L60B	50	60	80	100
L62B	70	100	120	140
L6A	130	240	340	400

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Hennepin County, Minnesota Table date: March 8, 2012

	60	110	150	180
L72A	60	110	150	180
L7A	100	180	250	310
L8A	110	210	290	360
L9A	50	70	90	110

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.