

Setback Distances in feet
 Mahnomon County, Minnesota Table date: February 3, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
36	50	50	60	70
59	150	210	230	250
63	130	180	200	220
121	60	80	110	130
125	50	60	70	90
180	50	60	80	90
191	160	250	340	400
205	130	210	280	350
236	50	70	90	100
296	60	90	110	140
344	60	80	100	110
346	60	80	100	120
426	150	210	230	250
540	50	70	80	90
543	50	110	200	290
544	50	70	90	110
737	60	80	100	120
746	50	70	80	90
748	60	90	110	130
749	60	100	140	180
767	50	70	90	110
1113	50	70	80	90
1139	110	210	290	370
1148	60	90	110	130
1149	50	70	90	110
1200	60	90	110	140
1804	60	80	100	130
1878	60	90	110	130
1967	50	70	90	110
1152B	140	230	310	380
1241B	150	250	330	400
127B	120	200	270	340
1825B	50	70	80	90
267B	60	90	120	140
33B	50	60	80	90

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
Mahnomon County, Minnesota Table date: February 3, 2012

352B	60	90	120	140
38B	50	70	90	100
40B	50	60	70	80
494B	50	70	90	100
718B	50	70	100	110
827B	60	90	120	140
967B	50	70	90	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.