

Setback Distances in feet
 McLeod County, Minnesota Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
35	90	140	190	230
86	50	50	70	80
109	50	60	70	80
112	50	50	60	70
113	50	60	80	90
114	50	60	70	90
118	50	70	80	100
239	50	60	80	90
247	140	240	320	340
255	90	190	270	350
269	50	50	60	70
313	50	50	60	80
336	50	50	70	90
362	50	50	60	70
386	50	70	90	100
392	120	220	300	380
414	50	60	70	80
517	50	100	140	180
539	50	70	90	120
956	50	50	70	80
978	50	60	70	80
1016	50	60	70	90
1016	50	60	70	90
1030	50	60	80	90
1075	50	60	70	90
1080	60	80	90	100
1084	60	90	120	140
1091	100	160	220	270
1092	50	50	60	80
1095	50	60	80	100
1228	110	210	280	360
1833	50	50	60	80
1834	50	50	60	80
102B	50	70	90	110
106B	50	60	80	90

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 McLeod County, Minnesota Table date: March 8, 2012

1204B	50	60	80	90
1207B	50	60	80	90
1213B	50	60	80	90
1229B	50	60	80	90
1901B	50	50	60	80
238B	50	80	100	110
27B	100	160	210	260
327B	140	220	290	360
39A	140	270	330	400
39B	150	270	370	400
41A	140	230	300	380
41B	140	230	300	380
611C	140	230	300	360
887B	50	70	100	120
920B	50	70	90	110
944B	50	60	80	90
945B	50	60	80	90
94B	50	70	90	110
L107A	50	70	90	100
L13A	60	90	120	140
L163A	50	60	80	100
L184A	50	50	50	60
L185B	50	50	50	50
L200A	50	80	90	100
L205A	80	120	140	160
L34A	50	50	50	60
L83A	50	60	80	90
L84A	50	60	70	90

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.