

Setback Distances in feet  
 Meeker County, Minnesota      Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
35	80	120	160	190
85	60	90	110	130
86	50	60	70	90
112	50	50	60	70
113	50	60	70	90
114	50	60	70	90
129	110	210	290	350
130	50	60	80	90
134	50	60	80	100
136	60	90	110	130
140	60	90	110	140
178	100	180	210	270
181	110	160	230	260
183	110	190	250	320
197	60	90	120	140
211	50	70	80	100
229	50	70	90	100
239	50	50	70	80
281	90	150	200	250
399	100	170	220	280
415	200	330	400	400
423	50	70	80	100
511	70	110	140	180
523	50	60	80	100
525	50	70	140	170
539	50	70	90	120
548	50	150	240	380
610	60	80	110	130
613	90	140	180	220
664	50	60	80	90
740	50	60	70	80
899	50	50	60	70
956	50	60	80	90
978	50	60	70	80
1015	120	210	280	340

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
 Meeker County, Minnesota      Table date: March 8, 2012

	50	60	70	90
1016	50	60	70	90
1080	60	90	110	120
1096	130	230	300	380
1097	130	230	310	390
1098	140	240	320	400
1099	100	140	180	220
1100	50	70	90	100
1101	50	60	80	90
1163	80	130	170	210
1165	50	90	130	160
1169	50	50	50	60
1173	50	70	140	170
1174	50	50	50	60
1175	90	130	170	210
1176	140	240	330	400
1178	70	110	150	190
1184	50	50	50	60
1185	90	140	190	230
1193	50	50	50	60
1197	60	90	110	130
1384	170	280	380	400
1385	50	60	80	90
1406	130	240	330	400
101B	60	90	110	130
102B	50	70	90	110
1159B	50	50	50	50
1162A	50	50	50	60
1162B	50	50	50	60
1204B	50	60	80	90
1383A	50	70	90	100
1387A	50	70	90	100
1391B	80	120	160	200
143B	80	120	150	190
1801B	80	130	170	210
286B	50	70	90	100
327A	140	220	290	360
327B	120	200	270	340
39A	160	300	400	400

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
 Meeker County, Minnesota      Table date: March 8, 2012

	41A	140	230	300	380
612B	80	130	170	210	
804B	70	120	160	200	
875B	150	240	310	380	
887B	50	70	90	110	
8B	130	200	260	320	
920B	50	70	90	110	
96B	50	70	90	100	
L107A	50	70	90	100	
L13A	60	90	120	140	
L163A	50	60	80	100	
L164A	50	70	80	100	
L179A	50	50	50	60	
L184A	50	50	50	60	
L185B	50	50	50	50	
L186A	50	50	60	60	
L186A	50	50	50	60	
L187A	60	90	100	120	
L191A	80	120	140	160	
L200A	50	80	90	100	
L205A	80	120	140	160	
L206B	50	50	50	50	
L307B	90	140	180	220	
L317A	60	110	160	200	
L318A	60	110	150	190	
L319A	60	100	140	180	
L321A	60	100	140	180	
L322A	70	120	160	200	
L323A	80	130	170	210	
L324A	80	110	150	170	
L324A	80	120	150	180	
L325A	70	110	150	180	
L326B	90	140	170	210	
L331A	60	120	170	220	
L332A	80	120	160	190	
L334A	50	70	140	170	
L335A	50	70	110	160	
L335A	50	70	110	160	

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
Meeker County, Minnesota      Table date: March 8, 2012

	50	100	140	180
L336A	50	100	140	180
L337B	90	140	180	220
L33A	50	50	50	60
L33B	50	50	50	60
L340B	90	140	180	220
L345A	80	140	180	220
L347A	50	90	130	160
L34A	50	50	50	60
L350A	60	110	150	180
L351A	50	70	140	170
L353B	80	130	170	210
L354A	90	140	190	230
L355B	80	120	150	180
L357B	80	120	150	180
L83A	50	60	80	90
L84A	50	60	70	90
L85A	50	60	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.