

Setback Distances  
Pipestone County, Minnesota      Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
J101B	50	60	80	100
J104A	50	60	80	90
J105A	170	290	400	400
J106B	50	70	80	100
J107A	50	60	80	90
J12A	160	300	400	400
J1A	50	50	70	80
J22A	140	220	290	360
J23A	50	80	100	120
J25A	50	80	110	130
J26B	50	70	90	100
J2A	50	80	100	120
J31B	170	290	400	400
J47A	50	60	80	90
J48A	50	60	80	100
J69A	150	290	400	400
J70A	50	150	260	360
J71A	50	60	70	80
J72B	140	220	290	360
J74A	150	270	370	400
J74B	150	270	370	400
J75A	140	250	340	400
J75B	140	250	340	400
J76A	50	50	60	70
J77A	50	80	100	120
J78A	50	60	70	80
J79B	50	50	60	80
J7A	100	180	240	300
J7B	100	180	240	300
J80A	50	80	100	120
J84A	70	120	170	210
J84B	70	120	170	210
J85A	90	180	250	320
J86B	50	50	60	80
J87A	50	70	90	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances  
Pipestone County, Minnesota      Table date: March 8, 2012

J88B	50	60	70	80
J89B	50	70	80	90
J90B	50	60	70	80
J91B	70	110	130	140
J93A	50	70	80	100
J94A	50	50	70	80
J96B	50	60	80	100
J99A	50	60	70	90
P11A	200	350	400	400
P11B	200	350	400	400
P12B	50	60	80	90
P14A	60	120	160	210
P14B	80	140	180	230
P16A	50	180	280	390
P20B	70	100	120	140
P24B	50	80	110	130
P27A	50	70	90	110
P28A	50	60	80	90
P29A	50	60	80	90
P30B	50	60	80	90
P32A	60	90	110	140
P33A	60	90	110	140
P34B	50	60	70	80
P34C2	50	50	60	70
P36A	100	190	260	330
P37B	170	270	360	400
P38B	130	220	290	360
P42A	50	80	100	120
P46	60	90	110	140
P48A	90	170	230	290
P48B	90	170	230	290
P4A	50	80	100	120
P56B	190	340	400	400
P5A	50	80	90	110
P8A	120	220	300	380

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.