

Setback Distances in feet
 Polk County, Minnesota Table date: February 3, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
47	60	90	110	130
59	150	210	230	250
65	160	210	230	250
111	140	220	280	350
236	50	70	90	100
296	60	90	110	140
348	120	200	270	330
372	130	210	270	340
387	50	70	90	110
412	150	240	330	350
426	150	210	230	250
435	100	150	190	230
439	140	190	210	230
450	70	100	130	160
481	130	240	260	280
506	50	70	90	110
540	50	70	80	90
543	50	110	200	290
544	50	70	90	110
547	170	270	360	400
563	90	130	150	180
565	130	210	240	270
582	50	70	90	110
641	50	80	100	120
642	60	90	110	130
643	150	210	230	260
645	150	210	230	260
647	150	210	230	260
650	60	80	90	110
651	140	210	230	250
670	60	90	110	120
671	70	110	140	170
681	70	110	150	180
704	160	270	370	400
712	150	260	360	400

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Polk County, Minnesota Table date: February 3, 2012

	713	130	190	210	230
	733	50	100	150	170
	737	60	80	100	120
	746	50	70	80	90
	749	60	100	140	180
	765	50	70	90	110
	767	50	70	90	110
	791	100	150	190	230
	908	60	90	110	130
	935	50	60	80	90
	1113	50	70	80	90
	1119	60	80	100	120
	1121	70	110	150	180
	1122	60	80	100	120
	1144	140	190	210	230
	1264	130	200	260	330
	1278	130	220	290	350
	1279	50	70	90	100
	1280	60	90	110	130
	1283	50	70	90	110
	1297	160	250	270	290
	1325	50	70	80	90
	1422	90	130	150	180
	1866	50	80	100	120
	1871	50	60	80	90
	1874	160	270	360	400
	1878	60	90	110	130
	1879	50	70	80	90
	1916	50	80	100	120
	1963	50	80	100	120
	1964	50	80	100	120
	1152B	140	230	310	380
	1304A	80	130	170	210
	1304B	80	130	170	210
	1315A	130	200	220	240
	1323B	70	100	130	150
	184A	50	70	90	110
	20B	60	90	110	130

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet
 Polk County, Minnesota Table date: February 3, 2012

	160	270	360	400
242B	160	270	360	400
258B	150	250	340	400
341B	170	290	380	400
38B	50	70	90	100
422A	50	70	90	110
422B	50	70	90	110
45B	160	240	320	390
45C	160	240	320	390
494B	50	70	90	100
57A	50	50	70	90
667B	60	100	130	150
67A	60	90	110	130
67B	60	90	110	130
707A	80	130	180	220
718B	50	70	100	110
735B	150	220	320	380
827B	60	90	120	140
93A	60	90	110	130
967B	50	70	90	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.