

Setback Distances in feet  
 Stearns County, Minnesota      Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
25	80	160	220	280
35	80	100	120	140
36	50	50	60	70
72	50	80	100	120
75	50	70	80	100
109	50	60	70	90
114	50	60	80	100
125	50	70	80	90
129	120	200	270	340
142	60	60	60	60
181	120	190	240	290
183	80	130	170	200
218	70	70	70	70
236	50	50	60	80
255	90	190	270	350
260	140	240	320	400
261	120	200	270	340
281	80	120	200	230
318	100	150	260	320
325	50	50	50	50
392	140	240	320	400
399	140	240	320	400
413	180	300	400	400
414	50	60	70	80
459	60	80	80	80
465	90	160	220	280
511	80	130	160	200
525	50	70	140	170
540	50	70	80	90
541	200	250	300	350
543	50	110	210	290
544	50	70	80	90
566	170	280	370	400
582	50	60	80	100
597	50	80	100	120

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
 Stearns County, Minnesota      Table date: March 8, 2012

873	60	60	60	60
1018	100	170	230	290
1055	50	70	80	90
1163	80	130	170	210
1805	90	130	170	210
1828	50	80	100	120
1842	60	60	60	60
1879	50	70	80	90
1879	50	70	80	90
1880	130	190	230	270
1892	50	50	50	50
133B	50	80	90	110
144B	60	90	110	130
155B	170	270	360	400
156A	120	210	290	370
156B	120	210	290	370
159B	90	140	170	210
179B	90	90	90	90
180A	50	60	80	90
180B	50	60	80	90
1825C	50	70	80	90
1902B	50	80	120	150
200B	60	80	110	130
204B	60	90	110	130
207B	150	240	310	380
233B	60	90	110	130
292B	60	90	110	130
327A	130	210	280	340
327B	130	210	280	340
32B	60	90	110	130
38B	50	60	70	90
406B	140	230	310	380
41A	140	230	300	380
41B	140	230	300	380
421B	50	70	80	100
446A	50	70	90	110
446B	50	70	90	110
454B	150	230	300	370

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
 Stearns County, Minnesota      Table date: March 8, 2012

461B	60	80	110	130
591B	50	60	80	90
5A	130	260	360	400
5B	130	260	360	400
639A	90	160	220	270
639B	100	170	230	280
7A	130	250	350	400
7B	130	250	350	400
875B	150	240	310	380
999B	50	70	80	100
L307B	90	140	180	220
L316B	70	130	180	230
L317A	60	110	160	200
L318A	60	110	150	190
L319A	60	100	140	180
L320A	50	70	80	90
L321A	60	100	140	180
L322A	70	120	160	200
L323A	80	130	170	210
L324A	80	120	150	180
L325A	70	110	150	180
L326B	90	140	170	210
L330A	50	70	80	90
L331A	50	70	80	90
L333A	80	120	160	190
L334A	50	70	140	170
L335A	50	70	110	160
L337B	90	140	180	220
L347A	50	90	130	160
L350A	60	110	150	180
L351A	50	70	140	170
L352A	50	70	80	90
L355B	80	120	150	180
L357B	80	120	150	180

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.