

Setback Distances in feet  
Waseca County, Minnesota      Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
L100B	50	70	80	100
L101C2	50	60	80	100
L102C2	50	60	80	100
L103A	90	140	190	240
L105C2	50	60	80	100
L106C2	50	60	80	100
L107A	50	70	90	100
L108A	50	70	80	100
L109A	50	60	80	100
L111A	50	70	90	110
L112A	50	70	80	100
L113B	50	70	90	100
L114A	60	100	140	170
L115A	50	70	90	100
L116A	50	60	80	90
L117C2	50	60	80	100
L118A	70	100	120	140
L119B	50	60	80	100
L120A	50	80	110	130
L121B	50	60	80	100
L122B	50	70	90	100
L123A	130	130	130	130
L124A	50	60	80	90
L125A	60	90	120	140
L126A	50	70	90	120
L127A	50	70	100	120
L128A	50	70	90	110
L129B	50	70	90	110
L130A	50	70	90	100
L13A	50	90	120	140
L14A	50	70	80	90
L15A	50	110	130	160
L26B	50	70	90	100
L36A	50	60	80	100
L40B	50	60	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
Waseca County, Minnesota      Table date: March 8, 2012

L41C2	50	60	80	100
L48A	50	50	70	90
L49A	50	70	80	90
L50A	50	70	80	90
L51C2	60	90	110	130
L57A	50	210	300	380
L5A	50	60	80	100
L63A	50	80	100	120
L64A	90	160	160	160
L73A	70	100	130	150
L74A	140	230	300	370
L75B	60	90	110	130
L76B	90	150	200	250
L77A	50	70	90	100
L78A	50	70	90	100
L79B	50	70	80	100
L80C2	50	60	80	100
L81A	50	70	80	100
L82A	50	60	80	100
L83A	50	60	80	90
L84A	50	60	70	90
L85A	50	60	80	100
L86A	60	80	110	130
L87A	60	90	120	140
L88A	50	80	100	120
L89A	50	60	80	90
L90A	50	60	80	90
L91A	50	70	90	110
L92A	120	200	280	350
L93A	50	110	140	170
L94A	80	110	140	160
L96B	140	230	300	370
L97C	130	230	300	370
L98A	50	60	80	100
L99B	50	70	80	100

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.