

Setback Distances in feet  
 Washington County, Minnesota      Table date: March 8, 2012

Map Unit Symbol	Drain Depth, feet			
	2	3	4	5
2	50	50	70	80
8	100	160	210	260
49	130	260	360	400
75	50	70	80	100
120	130	250	340	400
123	50	70	80	100
151	140	220	300	370
159	90	140	180	210
161	120	210	280	350
162	100	170	220	280
166	70	100	120	140
189	50	80	110	130
225	50	80	100	120
264	70	100	130	150
265	90	160	210	270
265	90	160	210	270
266	60	100	130	160
298	50	180	280	370
325	50	50	50	50
327	140	230	300	370
329	50	80	110	140
411	150	250	330	400
449	60	90	120	140
452	60	100	120	150
456	60	90	120	150
468	80	110	140	160
507	150	280	380	400
540	50	70	80	90
541	200	250	300	350
543	50	110	210	290
544	50	70	80	90
1055	50	70	80	90
1821	150	230	300	370
1847	70	190	280	370
12C	170	270	350	400

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.

Setback Distances in feet  
 Washington County, Minnesota      Table date: March 8, 2012

132B	50	60	70	90
151B	140	220	300	370
153B	70	100	130	160
155B	170	270	360	400
158B	130	190	250	310
159B	90	140	170	210
177B	100	150	190	230
1813B	140	220	290	350
259B	50	80	110	130
298B	50	180	280	370
2B	50	50	70	80
301B	60	90	120	150
302B	140	250	350	400
327B	140	230	300	370
342B	60	90	110	130
367B	60	90	110	130
411B	140	260	380	400
454B	150	240	320	390
49B	130	260	360	400
504B	50	60	70	90
7B	130	250	350	400
896C	150	240	320	390
8B	120	200	260	320

Notes: 1) These setback distances are only for the situation where a drainage system will be installed and the landowner wishes to avoid impacting the wetland hydrology. 2) These values assume the ponded water on the site is 0.25" or less. 3) The effective depth of the drain (ditch or tile) is the elevation difference between the ground surface at the approximate setback distance and the water surface in the drain, or the bottom of the drain if it typically has no standing water.